

# HYDRAULIC DOOR CLOSER 7000 SERIES

## International Standards



CANADA



U.S.A.



### INTERNATIONAL STANDARDS

This product is manufactured under a quality management system - BS 5750, ISO 9002, EN29002, CNS 12681, Z4034, JIS Z9901, and ASQC Q91.

Door Opening 180°

## Function and Features

- With standard, Backcheck, Hold-open or Fusible Link Hold-open Function.
- Efficient closing and latching is assured from an easily adjust the two speed control.
- Opening angle is possible up to 180°
- Reversible-left and right hand operation.
- Stable hydraulic fluid for any climatic operation and constant lubrication.
- 7000 series door closers are constructed with extruded anodised aluminium body, forged steel arms passivated against rust and high quality steel internal components.
- Closing speed can be used from -15°C to +40°C range.

**7002**  
**7003**  
**7004**




### Standard Colors

- Gold
- Silver
- Bronze



Models	Dimensions (mm)		
	7002	7003	7004
Closer Body (A)	207	207	207
Height (B)	55	55	55
Projection (C)	40	40	40



LATCHING SPEED

CLOSING SPEED

### Door Closer Selection Chart

S I Z E	Standard Arm installation			Parallel Arm Installation		Track Arm Installation		Back Check	Applicable Door Dimensions DW x DH (mm)	Maximum Door Weight (kg)
	Without Hold-Open	With Build In Hold-Open	With Hold-Open Arm	Without Hold-Open	With Build In Hold-Open	Without Hold-Open	With Hold-Open			
2	7002	S7002	7002H	P7002	P7002S	7002TA	7002TAH	7002BC	900 x 2100	50
3	7003	S7003	7003H	P7003	P7003S	7003TA	7003TAH	7003BC	1050 x 2100	65
4	7004	S7004	7004H	P7004	P7004S	7004TA	7004TAH	7004BC	1200 x 2100	85
5	7005	S7005	7005H	P7005	P7005S	7005TA	7005TAH	7005BC	1350 x 2100	110