

Technical features:

- Laquered polished brass removable faceplate and striker
- Zinc-plated steel case
- Reversible, nickel-plated silent action latch
- Nickel-plated bolt for latch dead-locking
- Nickel-plated cut-resistant dead-bolt, with a 25 mm. protrusion
- Anti-corrosion galvanised internal components

Supplied as standard:

- Striking plate
- Fixing screws
- Instruction sheet

Finishes:

- ON REQUEST: Satin stainless steel faceplate and striker (fin 20)

Standards:

- Locks with satin stainless steel faceplate and striker (finish 20), are certified fire-resistant by the American Underwrite Laboratories (UL LISTED R 14945(N))

Hand:
0 = Non-handed

Cylinder to be ordered separately

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim.	Hand	Fin.

- For entrance doors
- Dead-bolt and dead-locking latch
- OPERATION:
 - the latch-bolt is operated by handle or cylinder from either side
 - The dead-bolt is operated by cylinder from either side
- SUPPLIED AS STANDARD:
 - Square striking plate item 1.06106.20.0

1	85	22	60	0,910	1	1	52710 60 0
1	85	22	70	1,000	1	1	52710 70 0

- For classroom doors
- Dead-locking latch-bolt only
- Split spindle
- OPERATION:
 - The latch-bolt is operated by handle from either side
 - The outside handle may be activated or de-activated by cylinder
 - Reversible panic function
- SUPPLIED AS STANDARD:
 - Square striking plate item 1.06158.20.0

-	85	22	60	0,900	1	1	52760 60 0
-	85	22	70	1,000	1	1	52760 70 0

